

Electrical Specifications

Connector: SMA | Operating Temperature: -40° to +80° C

10 dB Coupler

Frequency Range (GHz)	Insertion Loss (-dB max)	Accuracy (-dB max)	Isolation A - B (-dB min)	Return Loss, I/P (dB min)	Return Loss, A (dB min)	Return Loss, B (dB min)	Part Number	Outline Drawing
5.60 - 8.80	1.0	+0.5/-1.0	20	18	16	12	692-560880-001	CS01
10.0 - 12.0	1.0	+0.5/-1.0	20	18	16	12	692-100120-001	CS01
12.7 - 15.4	1.0	+0.5/-1.0	20	18	16	12	692-127154-001	CS01
17.7 - 19.7	1.4	+0.5/-1.0	20	18	16	12	692-177197-001	CS01
21.2 - 23.6	1.4	+0.5/-1.0	20	18	16	12	692-212236-001	CS01

3 dB Splitter

Frequency Range (GHz)	Insertion Loss A (-dB max)	Insertion Loss B (-dB max)	Isolation A - B (-dB min)	Return Loss, I/P (dB min)	Return Loss, A (dB min)	Return Loss, B (dB min)	Part Number	Outline Drawing
5.60 - 8.80	3.7	3.7	20	18	16	16	592-560880-001	CS01
10.0 - 12.0	3.7	3.7	20	18	16	16	592-100120-001	CS01
12.7 - 15.4	3.7	3.7	20	18	16	16	592-127154-001	CS01

